

## ARO<sup>®</sup> PW20P-YPX-XXX EXP Pumps

- Upgrade to EXP from existing Wilden® P800 or PS800 pumps, or Versa-Matic® U2 pumps.
- ARO<sup>®</sup> pump matches the fluid inlet/outlet port dimensions of the pumps and it matches Wilden's mounting feet location.
- Leave the stalling issues and complex maintenance procedures behind.
- ARO<sup>®</sup> has the lowest total cost of ownership over the competition.

Ratio:	1:1				
Maximum GPM (LPM):	184 (696)				
Displacement per cycle Gallons (Liters):	1.4 (5.3)				
Air Inlet (Female):	3/4 - 14 N.P.T.				
Fluid Inlet/Outlet:	2" ANSI/DIN hybrid flange (center)				
Max. operating pressure psi (bar):	120 (8.3)				
Suspended solids max. dia. in. (mm):	1/4″ (6.4)				
Weight lbs (kg):	Polypropylene 89.0 (40.4) PVDF 116.8 (53)				
Maximum dry suction lift ft (m):	19.5 (5.9)				
Sound Level:	70 PSI 60 Cycles / Min 85.0 db(A)				



## Ordering

Position	1	2		3	4	5		6	7	8
Example:	PW20	Р	-	Y	Р	S	-	Х	Х	Х

Position 1 Model Series	Position 2 Center Section	Position 3 Connection	Position 4 Wetted Parts	Position 5 Hardware	<b>Position 6</b> Seat Material	Position 7 Ball Material	<b>Position 8</b> Diaphragm Material
PW20 - Standard Pump	P - Polypropylene	Y - 2" ANSI/DIN Hybrid Center Flange	K - PVDF P - Polypropylene	S – Stainless Steel	K - PVDF P - Polypropylene	A - Santoprene® C- Hytrel® G - Nitrile T - PTFE V - Viton®	A - Santoprene® C- Hytrel® G- Nitrile L - Long Life PTFE T - PTFE/ Santoprene® V - Viton®

Hytrel® is a registered trademark of DuPont company, Santoprene® is registered trademark of Monsanto, Viton® is a registered trademark of ExxonMobil, VERSA-MATIC® is a registered trademark of Versa-Matic Pump Company (IDEX Corp) and Wilden® is a registered trade name of Wilden Pump and Engineering Company, a Dover Resources Company.

## Accessories

Service Repair Kits | 637369 (air motor),

637373-XXX (fluid section with seats), 637374-X (major air valve assembly)

Flange Connection Kit | 67341-E20N

Diaphragm Failure Detection | Kit No.67237

Air Line Connection Kit | 66109 (Piggyback Filter/Regulator with gauge, pipe nipple and 5-foot air hose)



